

**LEAKTITE**

Engineering Specification

**1 Quart Mixing Container****LEAKTITE PART ID: 001Q02MM050****SPECIFICATIONS**

Top Outer Diameter: 4.625"  
 Top Out of Round: 1/16" Max  
 Height: 5.5625"  
 Wall Thickness: .025"  
 Weight: 1.4 oz  
 Overflow: 1 quart

← 4.625" →



5.5625"

← 3.375" →

**COMPONENTS**

Resin: High Heat High Density Polyethylene (HHDPE)  
 Color: Natural  
 Handle: No Handle

**PRINT SPECIFICATIONS**

Heat transfer label &amp; Offset Print

**CORRESPONDING LIDS**

Part & Description  
 #2M6 LID 1QT MMIX NAT

**STANDARD PACKAGING**

50 per pack  
 Pails packed top side up  
 Carton 4.50 pounds  
 160 Cartons Per Pallet = 8,000 bucket @ 757 pounds  
 Stretch Wrap: 75 guage or Higher  
 Wrap covers all 4 corners of the pallet.  
 Wrap applied with 3 full wraps at top & bottom

Color Options are available upon request

**FOOD SPECIFICATION**

This products does not meet food safety requirements.

**PALLET SPECIFICATIONS**

- 1) Pallet Type: Grade "A" - 4 Way
- 2) Pallet Size: 48"x40"
- 3) Pallet Tolerance: 48"x40", +1/4"/-1/2"
- 4) Minimum Bottom Boards: 5 per - min thickness of 5/8" - min spacing 3.5"
- 5) Notching Spacing: 6"
- 6) Max Spacing on Top Deck Boards - 3.25"
- 7) Minimum Stringer Size - Width 1.5" - Height 3.5" (+ or - 1/8")
- 8) No Broken Boards in use
- 9) Deck boards must be attached with a minimum of two 11-12 gauge, 2-1/4 inch helically or annually threaded nails, staggered, per connection.
- 10) Bottom Lead & Deck Board Width - minimum of 5.5"
- 11) Top & Bottom Board Thickness - 5/8"