

LEAKTITE

Engineering Specification

2.5 Quart Mixing Container**LEAKTITE PART ID: 2-5Q05M050****SPECIFICATIONS**

Top Outer Diameter: 6.625"
 Top Out of Round: 1/16" Max
 Height: 6"
 Wall Thickness: .030"
 Weight: 2.8 oz
 Overflow: 2.5 quart

**COMPONENTS**

Resin: High Heat High Density Polyethylene (HHDPE)
 Color: Natural
 Handle: No Handle

PRINT SPECIFICATIONS

Heat transfer label & Offset Print

CORRESPONDING LIDS

Part & Description
 #5M6 LID 1QT MMIX NAT

STANDARD PACKAGING

50 per pack
 Pails packed top side up
 Carton 9.55 pounds
 63 Cartons Per Pallet = 3,1500 bucket @ 632 pounds
 Stretch Wrap: 75 guage or Higher
 Wrap covers all 4 corners of the pallet.
 Wrap applied with 3 full wraps at top & bottom

Color Options are available upon request

FOOD SPECIFICATION

This products does not meet the food safety requirements.

PALLET SPECIFICATIONS

- 1) Pallet Type: Grade "A" - 4 Way
- 2) Pallet Size: 48"x40"
- 3) Pallet Tolerance: 48"x40", +1/4"/-1/2"
- 4) Minimum Bottom Boards: 5 per - min thickness of 5/8" - min spacing 3.5"
- 5) Notching Spacing: 6"
- 6) Max Spacing on Top Deck Boards - 3.25"
- 7) Minimum Stringer Size - Width 1.5" - Height 3.5" (+ or - 1/8")
- 8) No Broken Boards in use
- 9) Deck boards must be attached with a minimum of two 11-12 gauge, 2-1/4 inch helically or annually threaded nails, staggered, per connection.
- 10) Bottom Lead & Deck Board Width - minimum of 5.5"
- 11) Top & Bottom Board Thickness - 5/8"