

**LEAKTITE**

Engineering Specification

**5 Gallon .70 MIL Multi-Purpose Pail****LEAKTITE PART ID: 005GFNAT120****SPECIFICATIONS**

Top Outer Diameter: 11.875"

Top Out of Round: 3/16" Max

Height: 14.563"

Wall Thickness: 70MIL

Weight: 794 grams

Overflow: 5 US Gallons

← 11.875" →



14.563"

← 10.313" →

**COMPONENTS**

Resin: High Density Polyethylene (HDPE)

Color: Natural Color

Handle: 9 Gauge galvanized wire injection molded no-mark plastic grip

**STANDARD PACKAGING**

120 per pack (12 stacks of 10 each)

Pails packed top side up

Trays on top and bottom with stretch wrap &amp; pallet

Package Dimensions: 40"x48"x46.25

Stretch Wrap: 75 gauge or higher

Wrap covers all 4 corners of the pallet.

Wrap applied with 3 full wraps at top &amp; bottom

**PRINT SPECIFICATIONS**

Heat Transfer Label

Off-Set 4 Color Print

**CORRESPONDING LIDS**

Screw Top Lid &amp; Gamma Seal Lid

5GLD - 5 Gallon Lid w/Gasket

6GLD - 5 Gallon Easy Off Lid

Color Options are available upon request

**FOOD SPECIFICATION**

This product does not meet the food safety requirements.

**PALLET SPECIFICATIONS**

- 1) Pallet Type: Grade "A" - 4 Way
- 2) Pallet Size: 48"x40"
- 3) Pallet Tolerance: 48"x40", +1/4"/-1/2"
- 4) Minimum Bottom Boards: 5 per - min thickness of 5/8" - min spacing 3.5"
- 5) Notching Spacing: 6"
- 6) Max Spacing on Top Deck Boards - 3.25"
- 7) Minimum Stringer Size - Width 1.5" - Height 3.5" (+ or - 1/8")
- 8) No Broken Boards in use
- 9) Deck boards must be attached with a minimum of two 11-12 gauge, 2-1/4 inch helically or annually threaded nails, staggered, per connection.
- 10) Bottom Lead & Deck Board Width - minimum of 5.5"
- 11) Top & Bottom Board Thickness - 5/8"